

# FOX Talas 5 Luftdruck Setup ab 2014



32 mm							
26"			27.5"			29"	
Fahrgewicht KG	140mm	150mm	130mm	140mm	150mm	120mm	130mm
≤57	85 psi	80 psi	95 psi	85 psi	80 psi	80 psi	95 psi
57 - 61	95 psi	90 psi	105 psi	95 psi	90 psi	80 psi	105 psi
61 - 66	105 psi	95 psi	120 psi	105 psi	95 psi	90 psi	120 psi
66 - 70	120 psi	110 psi	130 psi	120 psi	110 psi	105 psi	130 psi
70 - 77	130 psi	120 psi	135 psi	130 psi	120 psi	120 psi	135 psi
77 - 84	135 psi	130 psi	145 psi	135 psi	130 psi	130 psi	145 psi
84 - 91	145 psi	145 psi	160 psi	145 psi	145 psi	135 psi	160 psi
91 - 98	160 psi	160 psi	175 psi	160 psi	160 psi	150 psi	175 psi
98 - 104	175 psi	175 psi	190 psi	175 psi	175 psi	160 psi	190 psi
104 - ≥113	190 psi	190 psi	200 psi	190 psi	190 psi	175 psi	190 psi

Empfohlener Neg. Federweg		
Federweg	15% sag (Hard)	20% sag (Soft)
140mm	21mm	28mm
150mm	22mm	30mm

Empfohlener Neg. Federweg		
Federweg	15% sag (Hard)	20% sag (Soft)
130mm	19mm	26mm
140mm	21mm	28mm
150mm	22mm	30mm

Empfohlener Neg. Federweg		
Federweg	15% sag (Hard)	20% sag (Soft)
120mm	18mm	24mm
130mm	19mm	26mm

32 mm						
26"			27.5"		29"	
Fahrgewicht KG	150mm	160mm	150mm	160mm	140mm	150mm
≤57	85 psi	85 psi	85 psi	85 psi	85 psi	75 psi
57 - 61	90 psi	90 psi	90 psi	90 psi	90 psi	85 psi
61 - 66	100 psi	100 psi	100 psi	100 psi	100 psi	90 psi
66 - 70	120 psi	120 psi	120 psi	120 psi	120 psi	110 psi
70 - 77	130 psi	130 psi	130 psi	130 psi	125 psi	120 psi
77 - 84	135 psi	135 psi	135 psi	135 psi	135 psi	125 psi
84 - 91	145 psi	145 psi	145 psi	145 psi	145 psi	145 psi
91 - 98	165 psi	165 psi	165 psi	165 psi	165 psi	165 psi
98 - 104	180 psi	180 psi	180 psi	180 psi	180 psi	180 psi
104 - ≥113	200 psi	200 psi	200 psi	200 psi	200 psi	200 psi

Empfohlener Neg. Federweg		
Federweg	15% sag (Hard)	20% sag (Soft)
150mm	22mm	30mm
160mm	24mm	32mm

Empfohlener Neg. Federweg		
Federweg	15% sag (Hard)	20% sag (Soft)
150mm	22mm	30mm
160mm	24mm	32mm

Empfohlener Neg. Federweg		
Federweg	15% sag (Hard)	20% sag (Soft)
140mm	21mm	28mm
150mm	22mm	30mm

32 mm				
Fahrgewicht KG	160/170/180mm	Empfohlener Neg. Federweg		
		Federweg	15% sag (Hard)	20% sag (Soft)
≤ 61	95 psi	160mm	24mm	32mm
61 - 66	105 psi	170mm	26mm	34mm
66 - 70	115 psi	180mm	27mm	36mm
70 - 77	125 psi			
77 - 84	135 psi			
84 - 91	145 psi			
91 - 98	155 psi			
98 - 104	165 psi			
104 - ≥113	175 psi			